



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 468 771 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
20.10.2004 Bulletin 2004/43

(51) Int Cl.7: **B23D 51/10**

(21) Application number: **04252091.6**

(22) Date of filing: **07.04.2004**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
HU IE IT LI LU MC NL PL PT RO SE SI SK TR**  
Designated Extension States:  
**AL HR LT LV MK**

(72) Inventor: **Shuhua, Sang**  
**Suzhou 215006 (CN)**

(74) Representative: **Stuttard, Garry Philip**  
**Urquhart-Dykes & Lord LLP**  
**Tower North Central**  
**Merrion Way**  
**Leeds LS2 8PA (GB)**

(30) Priority: **14.04.2003 CN 03221219**

(71) Applicant: **Positec Power Tools (Suzhou) Co., Ltd**  
**Suzhou 215006 (CN)**

(54) **Saw blade clamping device**

(57) The present invention relates to a quick-change saw blade clamping device which includes an output shaft (9), a cylindrical rotatable sleeve (1) and a torsion spring (8). The output shaft (9) is coupled to a blade carrier (4) which is disposed within the cylindrical rotatable sleeve (1). A rotatable member (7) is disposed within the cylindrical rotatable sleeve (1). A locking member

(5) pivotally connected to the blade carrier (4) lies in a guide groove which is formed on the blade carrier (4). A spiral surface (15) is formed on the front end of the rotatable member. When the cylindrical rotatable sleeve (1) is manually rotated, the spiral surface (15) urges the locking member (5) to press the blade into a locking position. The present invention provides an easily-operated clamping device of simple structure and small size.




FIG 4

EP 1 468 771 A1

## Description

[0001] The present invention relates to a blade clamping device for clamping the blade of (for example) a power saw such as a jigsaw or reciprocating saw.

[0002] CN-A-1217675 discloses a blade clamping device which disadvantageously needs to be riveted together. US-A-5165173 discloses a saw in which the blade is fixed to the drive shaft by means of fixing screws so that it is very inconvenient to remove the saw blade. In the blade clamping device of US-A-5324052, the blade is pressed by a spring-loaded clamping piece against a slot wall but the clamping device is very big and its operation is inconvenient.

[0003] The present invention seeks to improve blade clamping by providing a blade (eg saw blade) clamping device which allows a blade to be replaced quickly.

[0004] Thus viewed from one aspect the present invention provides a blade clamping device for clamping a blade comprising:

- a cylindrical rotatable sleeve having a proximal end in which is formed an aperture for a blade;
- a rotatable member mounted substantially coaxially within the cylindrical rotatable sleeve and having a proximal end;
- a blade carrier disposed within the cylindrical rotatable sleeve and having a proximal end in which is formed a blade receiving slot for the blade and a distal end;
- an output shaft coupled to the distal end of the blade carrier;
- a torsion spring for biasing the clamping device from a non-clamping configuration in which the blade is insertable into the blade carrier to a clamping configuration in which the blade is able to be clamped in the blade carrier;
- a guide groove radially and axially extending from an exterior surface of the blade carrier and communicating with the blade receiving slot;
- a locking member pivotally mounted in the guide groove on a pin; and
- a spiral surface disposed at the proximal end of the rotatable member,

wherein the cylindrical rotatable sleeve is manipulable rotationally from the clamping configuration to the non-clamping configuration whereat the aperture is aligned with the blade receiving slot for inserting in the blade in the blade carrier and wherefrom the cylindrical rotatable sleeve is automatically biased back to the clamping configuration by the torsion spring whereat the aperture is non-aligned with the blade receiving slot and the spiral surface positively engages a curved surface of the locking member giving the locking member a tendency to rotate about the pin thereby causing the locking member to positively engage the blade in the blade carrier.

[0005] The present invention is a quick-change saw

blade clamping device comprising an output shaft, a cylindrical rotatable sleeve and a torsion spring. The output shaft is coupled to a blade carrier which is disposed within the cylindrical rotatable sleeve. A blade receiving slot is formed on a front end of the blade carrier. An aperture is formed on a front end portion of the cylindrical rotatable sleeve. The cylindrical rotatable sleeve is integrally mounted to and disposed within the cylindrical rotatable sleeve. A guide groove radially and axially extends from an outer surface of the blade carrier and communicates with the blade receiving slot. A locking member is pivotally connecting to the blade carrier and disposed in the guide groove. A spiral surface is disposed at a front head end of the rotatable member and under a state in which a blade is clamped in a locking position, the spiral surface presses against the rear side surface of the locking member.

[0006] The present invention provides an easily-operated blade clamping device with a simple structure and small size which permits a blade to be quickly released and replaced.

[0007] The cylindrical rotatable sleeve may be manipulable rotationally by manual actuation of its exterior surface for which purpose the exterior surface may be provided with knurlings, a projection or a handle.

[0008] Preferably the cylindrical rotatable sleeve automatically rotates back from the non-clamping configuration to the clamping configuration by releasing the cylindrical rotatable sleeve.

[0009] Preferably when the locking member positively engages the blade in the blade carrier, the cylindrical rotatable sleeve is manipulable rotationally from the clamping configuration to the non-clamping configuration whereat the aperture is aligned with the blade receiving slot for releasing the blade (eg mechanically releasing the blade). Particularly preferably the blade is mechanically ejected.

[0010] Preferably the blade carrier rotatably contacts a front end surface of the rotatable member and a rear rod of the blade carrier passes through a central aperture of the rotatable member.

[0011] Preferably the torsion spring has a first end to which is connected the rotatable member and a second end to which is connected the output shaft.

[0012] Preferably a protrusive rib extends axially along the exterior surface of the rotatable member and a second retaining groove extends axially along the interior surface of the cylindrical rotatable sleeve, wherein the protrusive rib fits into the groove to securely retain the rotatable member and the cylindrical rotatable sleeve together.

[0013] Preferably two protrusive stoppers are provided on the ends of the spiral surface and an end portion of the blade carrier facing the spiral surface is provided with a limiting pin which is able to move between the protrusive stoppers.

[0014] Preferably the blade carrier has a proximal head on a distally extending rod and is disposed partly

within the cylindrical rotatable sleeve such that the distally extending rod passes through and out of the distal end of the rotatable member and the proximal head is slidably seated on the proximal end of the cylindrical sleeve. The guide groove extends substantially radially from the circumference of the proximal head and communicates with the blade receiving slot. The guide groove may be substantially rectangular. The proximal head may be essentially circular and the pin may be mounted along a chord of the proximal head.

[0015] Preferably the cylindrical rotatable sleeve and rotatable member are mounted substantially coaxially in a manner so as to prevent relative rotation. For this purpose, opposing faces of the cylindrical rotatable sleeve and rotatable member may be provided with engageable male and female portions. For example, an axial retaining rib in the exterior surface of the rotatable member may engage an axial retaining groove on the interior surface of the cylindrical rotatable sleeve.

[0016] To prevent relative axial movement of the cylindrical rotatable sleeve and rotatable member, a retaining element (eg a circlip) may be mounted circumferentially on the interior surface at or near to the distal end of the cylindrical rotatable sleeve.

[0017] Preferably the rotatable member has a cylindrical main body integrally formed at a proximal end with a cylindrical sleeve.

[0018] Preferably the surface of the proximal end of the cylindrical main body spirals axially along the interior of the cylindrical sleeve to define the spiral surface terminating at the proximal end of the cylindrical sleeve.

[0019] Preferably a first and a second protrusive stopper project radially inwardly from the proximal end of the cylindrical sleeve. In a particularly preferred embodiment, the device further comprises a limiting pin on the proximal head of the blade carrier, wherein said limiting pin engages the spiral surface along a path between the first protrusive stopper and the second protrusive stopper so as to limit the rotational range of the rotatable member in the clockwise and counter-clockwise direction.

[0020] In a preferred embodiment, the device further comprises a restoring member (eg spring) accommodated within the output shaft and capable of cooperating with the distal end of the blade, wherein when the blade is inserted in the blade carrier, the restoring member is biased with a tendency to eject the blade and when the blade is not inserted in the blade carrier, the restoring member is at rest. Preferably the restoring member cooperates with a force transmitting element (eg a U-shaped member) for ejecting the blade when the cylindrical rotatable sleeve is manually rotated from the clamping configuration to the non-clamping configuration.

[0021] Preferably the locking member is pivotal between a first position in the non-clamping configuration in which it is remote from the spiral surface and a second position in the clamping configuration in which it posi-

tively engages the spiral surface. Particularly preferably the locking member is capable of being pivoted between the first position and the second position by the insertion of the blade. Typically the blade is inserted manually in the non-clamping configuration.

[0022] In a preferred embodiment, the locking member is an irregular shape eg a substantially teardrop-shaped.

[0023] Viewed from a further aspect the present invention provides a saw comprising a blade clamping device as hereinbefore defined and a blade.

[0024] The present invention will now be described in a non-limitative sense with reference to the accompanying Figures in which:

Fig.1 is a perspective view of an embodiment of the present invention assembled with a blade;

Fig.2 is an exploded view of the essential parts of the embodiment of Fig. 1;

Fig.3 is a partial cross-sectional view of the embodiment of Fig. 1 in the clamping configuration (blade not inserted);

Fig. 4 is a partial cross-sectional view of the embodiment of Fig. 1 in the clamping position (blade inserted);

Fig.5 is a top cross-sectional view of Fig.4;

Fig.6 is a left view of Fig.3;

Fig.7 is a left view of Fig.4;

Fig.8 is a perspective view detailing a locking member of an embodiment of the present invention;

Fig.9 is a perspective view detailing a rotatable member of an embodiment of the present invention;

Fig.10 is a further perspective view detailing a locking member of an embodiment of the present invention;

Fig.11 is a perspective view detailing a blade carrier of an embodiment of the present invention;

Fig.12 is a further perspective view detailing a blade carrier of an embodiment of the present invention; and

Fig.13 is a perspective view detailing a cylindrical rotatable sleeve of an embodiment of the present invention.

[0025] Referring to Figs 1 and 2, an embodiment of the blade clamping device of the invention is illustrated comprising a rotatable member 7 mounted coaxially within a cylindrical rotatable sleeve 1. The rotatable member 7 has a cylindrical main body 7a integrally formed at a proximal end with a cylindrical sleeve 7b. A protrusive rib 12 extends axially along the exterior surface of the cylindrical sleeve 7b (see Fig. 9) and a second retaining groove 17 extends axially along the interior surface of the cylindrical rotatable sleeve 1 (see Fig. 5). The protrusive rib 12 fits into the second retaining groove 17 to securely retain the rotatable member 7 and the cylindrical rotatable sleeve 1 together. Additionally a circlip 24 is mounted in a groove formed on the interior

surface of the cylindrical rotatable sleeve 1 and engages the cylindrical sleeve 7b so as to retain the rotatable member 7 axially within the cylindrical rotatable sleeve 1 (ie the circlip 24 prevents axial movement).

[0026] A blade carrier 4 having a proximal head 4a on a distally extending rod 4b is disposed partly within the cylindrical rotatable sleeve 1 such that the distally extending rod 4b passes through and out of the distal end of the rotatable member 7 and the proximal head 4a is slidably seated on the proximal end of the cylindrical sleeve 7b. A blade receiving slot 14 for receiving a blade 3 is defined in the proximal head 4a (see Figs 6, 11 and 12) and an aperture 13 in the proximal end of the cylindrical rotatable sleeve 1 extends across the blade receiving slot 14 (see Figs. 6, 7 and 13). An output shaft 9 is coupled by a pin 22 to the distally extending rod 4b. A first end of a torsion spring 8 is connected to the rotatable member 7 and a second end of the torsion spring 8 is connected to the output shaft 9.

[0027] Referring to Figs 4 and 9, the surface of the proximal end of the cylindrical main body 7a spirals axially along the interior of the cylindrical sleeve 7b to define a spiral surface 15 terminating at the proximal end of the cylindrical sleeve 7b. Two protrusive stoppers 16, 19 project radially inwardly from the proximal end of the cylindrical sleeve 7b. A limiting pin 18 on the proximal head 4a of the blade carrier 4 engages the spiral surface 15 along a path between the protrusive stopper 16 and the protrusive stopper 19 so as to limit the rotational range of the rotatable member 7 in the clockwise and counter-clockwise direction relative to the blade carrier 4.

[0028] A guide groove 10 extends radially from the exterior surface of the proximal head 4a of the blade carrier 4 into the blade receiving slot 14. An irregular-shaped locking member 5 capable of engaging the spiral surface 15 is pivotally mounted in the guide groove 10 by means of a pin 6 (see Fig. 8). An end cap 23 for the cylindrical rotatable sleeve 1 has a rib 26 which cooperates with a first retaining groove 11 formed on the cylindrical rotatable sleeve 1. A spring 21 accommodated within the output shaft 9 cooperates with a force transmitting element 25 for elastically ejecting the saw blade 3 on release.

[0029] Referring to Figs. 3 to 7, a projection 2 which extends radially from the exterior surface of the cylindrical rotatable sleeve 1 is manipulated rotationally to a position in which the aperture 13 of the cylindrical rotatable sleeve 1 is aligned with the a blade receiving slot 14 of the blade carrier 4 (see Fig.6) and in which the torsion spring 8 is then under tension. A saw blade 3 is inserted into the blade receiving slot 14 and pressed against the force transmitting element 25 so as to compress the spring 21. When the projection 2 is released and the cylindrical rotatable sleeve 1 seeks to return to its initial position under the force of the torsion spring 8, the spiral surface 15 of the rotatable member 7 engages the edge of the locking member 5 causing the locking

member 5 to rotate about the pin 6 and impinge on the saw blade 3. At the same time, the aperture 13 of the cylindrical rotatable sleeve 1 is disaligned with the a blade receiving slot 14 ie the aperture 13 of the cylindrical rotatable sleeve 1 is disaligned with the saw blade 3 (see Fig.7) so that the blade projections 20 are tightly clamped against the interior face of the proximal end of the cylindrical rotatable sleeve 1. As such, the saw blade 3 will be securely locked within the clamping device.

[0030] Referring to Figs. 3-7, the projection 2 is manually rotated to a position in which the aperture 13 is again aligned with the blade receiving slot 14 (see Fig. 6) and the saw blade 3 will be ejected from the clamping device under the elastic restoring force of the spring 21 without injuring the operator with a hot saw blade just after working.

#### Claims

1. A blade clamping device for clamping a blade (3) comprising:

- a cylindrical rotatable sleeve (1) having a proximal end in which is formed an aperture (13) for a blade (3);
- a rotatable member (7) mounted substantially coaxially within the cylindrical rotatable sleeve (1) and having a proximal end;
- a blade carrier (4) disposed within the cylindrical rotatable sleeve (1) and having a proximal end (4a) in which is formed a blade receiving slot (14) for the blade (3) and a distal end;
- an output shaft (9) coupled to the distal end of the blade carrier (4);
- a torsion spring (8) for biasing the clamping device from a non-clamping configuration in which the blade is insertable into the blade carrier (4) to a clamping configuration in which the blade is able to be clamped in the blade carrier (4);
- a guide groove (10) radially and axially extending from an exterior surface of the blade carrier (4) and communicating with the blade receiving slot (14);
- a locking member pivotally mounted in the guide groove on a pin (6); and
- a spiral surface (15) disposed at the proximal end of the rotatable member (7),

wherein the cylindrical rotatable sleeve (1) is manipulable rotationally to the non-clamping configuration whereat the aperture (13) is aligned with the blade receiving slot (14) for inserting the blade (3) into the blade carrier (4) and wherefrom the cylindrical rotatable sleeve (1) is biased back to the clamping configuration by the torsion spring (8) whereat the aperture (13) is non-aligned with the

- blade receiving slot (14) and the spiral surface (15) positively engages a curved surface of the locking member (5) giving the locking member (5) a tendency to rotate about the pin (6) thereby causing the locking member (5) to positively engage the blade (3) in the blade carrier (4).
2. A device as claimed in claim 1 wherein when the locking member (5) positively engages the blade (3), the cylindrical rotatable sleeve (1) is biased back from the clamping configuration to the non-clamping configuration by releasing the cylindrical rotatable sleeve (1).
  3. A device as claimed in claim 1 or 2 wherein the cylindrical rotatable sleeve (1) is manipulable rotationally from the clamping configuration to the non-clamping configuration whereat the aperture (13) is aligned with the blade receiving slot (14) for releasing the blade (3).
  4. A device as claimed in any preceding claim, wherein the blade carrier (4) rotatably contacts a front end surface of the rotatable member (7) and a rear rod of the blade carrier (4) passes through a central aperture of the rotatable member (7).
  5. A device as claimed in any preceding claim, wherein the torsion spring (8) has a first end to which is connected the rotatable member (7) and a second end to which is connected the output shaft (9).
  6. A device as claimed in any preceding claim, wherein a protrusive rib (12) extends axially along the exterior surface of the rotatable member (7) and a second retaining groove (17) extends axially along the interior surface of the cylindrical rotatable sleeve (1), wherein the protrusive rib (12) fits into the groove (17) to securely retain the rotatable member (7) and the cylindrical rotatable sleeve (1) together.
  7. A device as claimed in any preceding claim, wherein two protrusive stoppers (16, 19) are provided on the ends of the spiral surface (15) and an end portion of the blade carrier (4) facing the spiral surface is provided with a limiting pin (18) which is able to move between the protrusive stoppers (16, 19).
  8. A device as claimed in any preceding claim wherein the cylindrical rotatable sleeve (1) and rotatable member (7) are mounted substantially coaxially in a manner so as to prevent relative rotation.
  9. A device as claimed in any preceding claim, wherein the rotatable member (7) has a cylindrical main body (7a) integrally formed at a proximal end with a cylindrical sleeve (7b).
  10. A device as claimed in claim 9, wherein the blade carrier (4) has a proximal head (4a) on a distally extending rod (4b) and is disposed partly within the cylindrical rotatable sleeve (1) such that the distally extending rod (4b) passes through and out of the distal end of the rotatable member (7) and the proximal head (4a) is slidably seated on the proximal end of the cylindrical sleeve (7b).
  11. A device as claimed in claim 9 or 10, wherein the surface of the proximal end of the cylindrical main body (7a) spirals axially along the interior of the cylindrical sleeve (7b) to define the spiral surface (15) terminating at the proximal end of the cylindrical sleeve (7b).
  12. A device as claimed in claim 9, 10 or 11, wherein a first and a second protrusive stopper (16, 19) project radially inwardly from the proximal end of the cylindrical sleeve (7b).
  13. A device as claimed in claim 12 further comprising a limiting pin (18) on the proximal head (4a) of the blade carrier (4), wherein said limiting pin (18) is movable between the first protrusive stopper (16) and the second protrusive stopper (19) so as to limit the rotational range of the rotatable member (7).
  14. A device as claimed in any preceding claim further comprising a restoring member (21) accommodated within the output shaft (9) and capable of cooperating with the distal end of the blade (3), wherein the restoring member (21) in the clamping configuration is biased towards ejecting the blade (3) and in the non-clamping configuration is at rest.
  15. A device as claimed in claim 14 wherein the restoring member (21) cooperates with a force transmitting element (25) for ejecting the blade (3) on manipulation rotationally from the clamping configuration to the non-clamping configuration.
  16. A device as claimed in any preceding claim wherein the locking member (5) is pivotal between a first position in the non-clamping configuration in which it is remote from the spiral surface (15) and a second position in the clamping configuration in which it positively engages the spiral surface (15).
  17. A device as claimed in claim 16 wherein the locking member (5) is capable of being pivoted between the first position and the second position by the insertion of the blade (3).
  18. A device as claimed in claim 1 wherein the locking member (5) is an irregular shape.
  19. A device as claimed in claim 18 wherein the locking

member (5) is substantially teardrop-shaped.

20. A saw comprising a blade clamping device as claimed in any preceding claim and a blade (3).

5

21. A quick-change saw blade clamping device comprising an output shaft (9), a rotatable sleeve (1), and a torsion spring (8), said output shaft (9) is coupled to a blade carrier (4) which is disposed within said rotatable sleeve (1), a blade receiving slot (14) is formed on a front end of said blade carrier (4), a aperture (13) is formed on a front end portion of said rotatable sleeve (1), **characterized in that** said rotatable sleeve (7) is integrally mounted to and disposed within said rotatable sleeve (1), a guide groove (10) radially and axially extending from an outer surface of said blade carrier (4) and communicating with said a blade receiving slot (14), a locking member (5) is pivotally connecting to said blade carrier (4) and disposed in said guide groove (10), a spiral surface (15) disposed at a front head end of said rotatable member (7), under a state in which a blade clamped in a locking position, said spiral surface presses against the rear side surface of said locking member (5).

10

15

20

25

30


35

40

45

50

55






FIG 3













FIG 4











European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 04 25 2091

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	GB 2 322 593 A (BOSCH GMBH ROBERT) 2 September 1998 (1998-09-02) * column 4, line 11 - column 55 * * figure 1 *	1,21	B23D51/10
D,A	& CN 1 217 675 A (BOSCH GMBH ROBERT) 26 May 1999 (1999-05-26) -----	1,21	
A	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 06, 22 September 2000 (2000-09-22) -& JP 2000 084729 A (MAKITA CORP), 28 March 2000 (2000-03-28) * abstract * * figures 17-23 *	1,21	
A	US 6 112 420 A (SCHICKERLING JASON) 5 September 2000 (2000-09-05) * the whole document *	1,21	
P,A	WO 03/099523 A (POSITEC POWER TOOLS SUZHOU CO ; BIN ZHANG (CN); CHENGDAO LI (CN)) 4 December 2003 (2003-12-04) * page 7, line 1 - page 13, line 24 * * figures 4-8,11-13,15-19 * -----	1,21	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B23D
Place of search		Date of completion of the search	Examiner
The Hague		6 August 2004	Chariot, D
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.02 (Pou/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 04 25 2091

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-08-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2322593	A	02-09-1998	CN 1217675 A	26-05-1999
			CN 1217675 T	26-05-1999
			DE 69814280 D1	12-06-2003
			WO 9838000 A1	03-09-1998
			EP 0906166 A1	07-04-1999
			JP 2000509665 T	02-08-2000
			US 6308425 B1	30-10-2001
CN 1217675	A	26-05-1999	GB 2322593 A	02-09-1998
			CN 1217675 T	26-05-1999
			DE 69814280 D1	12-06-2003
			WO 9838000 A1	03-09-1998
			EP 0906166 A1	07-04-1999
			JP 2000509665 T	02-08-2000
			US 6308425 B1	30-10-2001
JP 2000084729	A	28-03-2000	NONE	
US 6112420	A	05-09-2000	DE 10036171 A1	22-02-2001
			JP 2001062627 A	13-03-2001
WO 03099523	A	04-12-2003	CN 1461684 A	17-12-2003
			WO 03099523 A2	04-12-2003

EPO FORM P0458

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82